

RIDGID PRESSING RANGE

A SUPPORT GUIDE FOR
▶ RIDGID STRUTSLAYR

BY EVELYNN VERDYCK – DECEMBER 2023

©2019, RIDGID, Inc. The Emerson logo and RIDGID logo are registered trademarks of Emerson Electric Co. or RIDGID, Inc. in the U.S. and other countries. All other trademarks belong to their respective holders.



Launch Product
Information



Product Selection Aids



Order information



**DELIVER A QUALITY, BURR-FREE
CUT IN 5 SECONDS OR LESS.**

RIDGID PRESSING | STRUTSLAYR

RIDGID



- FAB SHOP QUALITY WITH **BURR-FREE CUTS**
- CLEAN, CONSISTENT CUTS **IN 5 SECONDS OR LESS**
- SHEAR CUT = **SPARK FREE CUTS**
- **EASY TO MOVE AROUND THE JOB SITE & MOUNTS TO RIDGID TRISTAND**
- **BUILT-IN MEASURING GUIDE ALLOWS ACCURACY OF CUT ON JOB SITE**

RIDGID PRESSING | RP 350 & RP 351

RIDGID



- FORCE OUTPUT OF **32 KN**
- PRESS CAPACITY 12 to 108 MM
- **SPEED PRESS** - CYCLE TIME OF <54MM IN 3 TO 4 SECONDS, CAPABLE TO PRESS 54 MM IN 5 SECONDS
- **BRUSHLESS MOTOR, ADVANCED HYDRAULIC SYSTEM** ALLOWS 100K PRESS CYCLES WITH NO SCHEDULED MAINTENANCE
- SMART TOOL WITH BLUETOOTH INTEGRATION
- INFINITE SWIVEL HEAD
- COMPATIBLE WITH **STRUTSLAYR**


RIDGID PRESSING | STRUTSLAYR COMPATIBILITY



Strut of
41 x 41 mm
(Nominal)



Model: FUS 41
Thickness:
1.5 / 2.0 / 2.5 mm
Finish:
Sendzimir Galvanized



Model: MQ-41 (U/L)
Thickness:
1.5 / 2.0 / 2.5 mm
Finish:
Pre-Galvanized



Model: MPR
Thickness:
1.5 / 2.0 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized



Model: Strut Framing
Channel
Thickness:
1.5 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized
Hot-Rolled Mild Steel



Model: RAPIDSTRUT 41 (L/H),
BUP1000 41 (L/H), PG41 (L/H)
Thickness:
1.5 / 2.0 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized



Model: VARIFIX C
Thickness:
1.5 / 2.0 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized



Model: P1000H, P1000T
Thickness:
1.5 / 2.0 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized



Strut of
21 x 41 mm
(Nominal)



Model: FUS 21
Thickness:
1.5 / 2.0 / 2.5 mm



Model: MPR
Thickness:
1.5 / 2.0 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized



Model: Strut Framing
Channel
Thickness:
1.5 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized
Hot-Rolled Mild Steel



Model: RAPIDSTRUT 21 (L/H),
BUP1000 21 (L/H), PG21 (L/H)
Thickness:
1.5 / 2.0 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized



Model: P3300T, P4000T
Thickness:
1.5 / 2.0 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized

⊗ Not for use with Stainless Steel Strut
1.4404 / RVS 304 / SS316L



StrutSlayR is capable of cutting many other brands throughout Europe - please refer to RIDGID technical help for full compatibility listing.
Strut Specifications are subject to changes without prior notice, always pay attention. We cannot be accountable for the information disclosed herein.

RIDGID PRESSING | STRUTSLAYR COMPATIBILITY



Strut of
41 x 41 mm
(Nominal)




Model: Railstrut R441
Thickness:
2.0 / 2.5 mm
Finish:
Sendzimir Galvanized
Hot-Dip galvanized
Standard Finish



Model: R41S / SP
Thickness:
1.5 / 2.5 mm
Finish:
Hot-Dip Galvanized
Sendzimir Galvanized




Model: Rail 41 x 41 LG
Thickness:
2.0 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized



Model: Strut 41x41
Thickness:
2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized
Plain Oil Finish
Sendzimir Galvanized



Model: SZ-MF / A15HD /
A25HD
Thickness:
1.5 / 2.0 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized



Model: KHAL 41 / KHA 41
Thickness:
1.5 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized



Model: MS4125PG / MS4115PG
Thickness:
1.5 / 2.0 / 2.5 mm
Finish:
Pre-Galvanized,



Strut of
21 x 41 mm
(Nominal)




Model: Railstrut R421
Thickness:
2.0 / 2.5 mm
Finish:
Sendzimir Galvanized
Hot-Dip galvanized
Standard Finish



Model: R21SP
Thickness:
2.0 mm
Finish:
Hot-Dip Galvanized
Sendzimir Galvanized




Model: Rail 21 x 41 LG
Thickness:
2.0 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized



Model: Strut 21x41
Thickness:
2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized
Plain Oil Finish
Sendzimir Galvanized



Model: SZ-MG
Thickness:
1.5 / 2.0 / 2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized



Model: KHA 21
Thickness:
2.5 mm
Finish:
Pre-Galvanized,
Hot-Dip Galvanized



Model: MS2115 / MS2125PG
Thickness:
1.5 / 2.5 mm
Finish:
Pre-Galvanized,

⊗ Not for use with Stainless Steel Strut
1.4404 / RVS 304 / SS316L



StrutSlayR is capable of cutting many other brands throughout Europe - please refer to RIDGID technical help for full compatibility listing.
Strut Specifications are subject to changes without prior notice, always pay attention. We cannot be accountable for the information disclosed herein.

RIDGID PRESSING | STRUTSLAYR COMPATIBILITY



Strut of
41 x 41 mm
(Nominal)


korA[®]
HIGH PERFORMANCE FIXINGS



Model: KORA 41 X 41MM
Thickness: 2.5 mm
Finish: Pre-Galvanised
Zinc-plated $\geq 19\mu\text{m}$



Strut of
21 x 41 mm
(Nominal)



Model: KORA 41 X 21MM
Thickness: 2.5 mm
Finish: Pre-Galvanised
Zinc-plated $\geq 19\mu\text{m}$



REQUIRE **SUPPORT?**

RIDGID

PRODUCT MANAGER, **PLUMBING PRESSING RIDGID**

Evelynn Verdyck

Evelynn.Verdyck@Emerson.com

+32 11 598 613

ALL ASSETS AVAILABLE ON
DROPBOX